

## Technical data sheet Basic

Product description	vinyl flooring with a rigid composite core and an attached acoustic underlayment complies with EN14041:2004+AC:2006	
Technology	SPC Stone Polymer Composite	
Dimensions	1220 x 181 mm	
Thickness	3,5 mm + 1 mm of integrated pad (4,5 mm total)	
Wear layer thickness	0,3 mm	
Bevel	4 side microbevel	
Installation method	floating installation, glueless system Valinge 2G	
Waterproof	yes	
Packaging	2,871 m <sup>2</sup>	
Class of use - Residential areas	EN 685	23 (warranty period: 10 years)
Class of use - Commercial areas	EN 685	32 (warranty period: 3 years)
Reaction to fire	EN 13501	B <sub>fl</sub> -s1
Wear resistance	EN ISO 660-2	T group
Residual indentation	EN ISO 24343-1	0,01 mm
Dimensional stability	EN ISO 23999:2008	0,05%
Slip resistance	EN 13893	DS
Resistance to stain and chemicals	EN ISO 26987	Index 0 (very good)
Light fastness	EN ISO 105-B02	≥ 6
Thermal resistance	EN 12667	0,038 m <sup>2</sup> K/W
Underfloor heating	EN 12524/12667	yes - max 27°C
Content of pentachlorophenol	EN 14041 Anex B	not found
Formaldehyde emission	EN 717-1	E1
Impact sound reduction	EN ISO 717-2:2013	ΔL <sub>w</sub> = 19 dB
VOC		A+

### Dom Korkowy Sp. z o.o.

30-198 Kraków, ul. Balicka 255

tel. 0048 12 6379639

marketing@domkorkowy.pl